



*The future is clean air ... the future is Sourcetec*

www.sourcetecindustries.com E-mail: sales@sourcetecindustries.com

Tel: (905) 678-9333 1-800-784-2383 Fax: (905) 678-7133

PROJECT :

LOCATION :

ARCHITECT/ENG :

CONTRACTOR :

SALES ENG/DIST :

DATE :

## STANDARD HIGH TEMPERATURE EXHAUST HOSE SOURCETEC HOSE SERIES 100 TYPE 8100

### Description:

Type 8100 hose is a 2 ply hose of woven fiberglass and coated with silicone rubber. A helically wound spring steel wire is embedded between the plies, the whole assembly is double wound with a treated fibreglass cord and heat vulcanized to provide greater strength.

### Applications:

- \* vehicle exhaust fumes
- \* machine and engine manufacturing
- \* hot plant air removal
- \* combustion by-products

### Properties:

- \* high temperature resistant
- \* smooth interior for maximum air flow
- \* non-kinking
- \* good chemical resistance

### RECOMMENDED FOR:

OVERHEAD EXHAUST SYSTEMS  
TRUCK EXHAUST

\*\*THIS HOSE IS NOT RECOMMENDED FOR HOSE REEL APPLICATIONS PLEASE USE OUR 9100 SERIES HOSE\*\*

### Temperature Properties

**- 80F Degrees**  
to  
**+600F Degrees Continuous**

Intermittant temperature is higher  
consult factory

\*Hose is subject to technical changes and color variations

ITEM	QTY	MODEL	DESCRIPTION	NOTES

We reserve the right to change specification and details without prior notice. This drawing is sole property of Sourcetec Industries Inc.  
Unauthorized duplication, distribution or use by third party is strictly prohibited.

FORM 3