



The future is clean air ... the future is Sourcetec

www.sourcetecindustries.com E-mail: sales@sourcetecindustries.com

Tel: (905) 678-9333 1-800-784-2383 Fax: (905) 678-7133

PROJECT :

LOCATION :

ARCHITECT/ENG :

CONTRACTOR :

SALES ENG/DIST :

DATE :

**OUR STANDARD HIGH TEMPERATURE EXHAUST HOSE
FOR HOSE REELS
SOURCETEC HOSE SERIES 100 TYPE 9100**

Description:

Type 9100 hose is a 2 ply hose of woven fiberglass and coated with silicone rubber. Hose comes with a NOMEX sleeve for extra outside protection. A helically wound spring steel wire is embedded between the plies, the whole assembly is double wound with a treated fibreglass cord and heat vulcanized to provide greater strength.

RECOMMENDED FOR:

EXHAUST HOSE REELS
TRUCK EXHAUST

Applications:

- * vehicle exhaust fumes
- * hose reel exhaust systems
- * military and commercial requirements
- * chemical and plastic industries

Temperature Properties

**- 80F Degrees
to
+600F Degrees Continuous**

Intermittant temperature is higher
consult factory

Properties:

- * high temperature resistant
- * low temperature flexibility, high temp stability
- * non-kinking
- * good chemical resistance

*Hose is subject to technical changes and color variations

ITEM	QTY	MODEL	DESCRIPTION	NOTES

**We reserve the right to change specification and details without prior notice. This drawing is sole property of Sourcetec Industries Inc.
Unauthorized duplication, distribution or use by third party is strictly prohibited.**

FORM 3