



The future is clean air ... the future is **Sourcetec**[®]

SDC Filter Unit

SDC-600 SERIES




Inlet Duct

STANDARD FEATURES

- 1 HP, 110/1/60 Voltage, TEFC Motor
- Air Flow of 825 cfm
- Spark Resistant Wheel
- Self Cleaning Wheel
- 55 Gallon Drum
- Spark Trap
- Prefilter
- Efficiency 99.9994% at 1 micron
- 6" Diameter Intake
- Start/Stop with 10ft.cord/plug
- Quick Release Clamps for Access to Filter
- Clean Out Door with Quick Disconnect
- Handles
- CSA & UL Approved
- Meets & Exceeds OSHA Requirements

OPTIONS

- Fan Intake Quick Disconnect



Flexible Hoses


- 5"x 5 FT
- 6"x 5 FT

*More sizes available upon request

- Special Fittings and Adaptors



Flexible Arm Series SAL



4 Wheel Castor Base

RECOMMENDED FOR

- Buffing
- Sanding
- Woodworking
- Grinding
- Polishing
- Cleaning

BENEFITS

- Practical
- Compact
- Light Weight
- Portable
- Low Cost



The future is clean air ... the future is **Sourcetec**[®]

We reserve the right to change specifications without notice.

Sourcetec Industries Inc.

Ontario, Canada

Tel: (905) 678-9333 Fax: (905) 678-7133

Ohio, USA

1-800-784-2383

www.sourcetecindustries.com

E-mail: sales@sourcetecindustries.com